

Zhiguang Digital All Liquid Cooling industrial and Commercial Energy Storage System (110kW/233kWh)



Features

- Ultimate modularity and standardized design
- PACK and PCS dual channel liquid cooling
- Flexible layout combination, can be extended to 10 cabinets, back to back, 10 x 20 foot combination 3.13 megawatt hours
- BMS, PACK, Cabinet, three-level safety, inspection and big data analysis warning
- Battery, PACK, and cabinet three-level pressure relief system
- Networked, EMS energy management, and cloud based big data lifecycle management based on the 5S fully digital concept

Basic	
Configuration	IP260S
Number of Pack	5
Short-circuit current	12.2kA
Electrical	
Rated charging Current	145A
Max. Charging Current	160A, lasts 1minute
Nominal Capacity	233KWH
Voltage Range	728~949V
Nominal Voltage	832V
Max. continuous current	140A
Rated Power	100kW(0.5P)
Auxiliary Power	
Cooling Unit Power	Cooling:8KW,
Voltage Range	176~250V
BMS Power	60W
System	
Anticorrosion	C5
IP rating	Battery:IP66,Control:IP65,NEMA 3R
Power connection	Fast Plug
Grounding Mode	≤ 4Ω, Meet the Local Scope Requirements
Cooling Mode	Liquid Cooling
Storage Environment Temperature	-50~60 °C
Operating Environment Temperature	-25 ~55 °C
Environment Humidity	RH≤95% (Non-Condensing)
Altitude Requirements	< 4000m (> 3000m Derating)
Dimension	1530*1300*2330mm
Weight	3000kg
Color	RAL 7035
PCS	
Basic	
Rated Power	100kVA
Overload Capability	Constant Operation@110%, 1min@120%
Efficiency	99%
Power Response time	<20ms
Charge/Discharge Switching Time	<50ms
Operating Environment Temperature	-40 ~ 45°C (50°C with Cooling)
Installation	Wall Mounted
IP rating	IP66
Cooling Mode	Liquid Cooling
Isolation Method	Non-Isolated
DC side	
Max. Voltage	1000V
Operating Voltage Range	600 ~ 1000V
Full Load Operating Voltage Range	600 ~ 1000V
AC side	
Rated Voltage	380V
Rated Current	145A
Max. Long-Term Operating Current	173A
Voltage Range	±15%
Frequency	50/60Hz±5Hz
Total Current Harmonics	< 3%
Communication	
Communications Interface	wireless 4G/3G/RJ45/RS485
Communications Protocol	Modbus-RTU/Modbus-TCP



Guangdong Zhiguang Electronic Co., Ltd

Add: No. 89, Ruibo Road, Huangpu District, Guangzhou, P.R.China

Tel: 020-83909333

Fax: 020-83909333

Web: www.gzzg.com.cn